

Flash Profoto D2 500 air TTL (321 EUR)



Luogo **Puglia, Lecce**
<https://www.annunci.it/x-244169-z>

New, never used!!!!

D2 500 AirTTL
Overview
Product number
330178

Popular applications
Portrait, Sports and action, Still life

Recommended for
Studio and high volume photography

Flash
Max energy
500 Ws

Energy range
10 f-stops (0.5 - 500 Ws)

Energy control increments

 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL	 https://www.annunci.it/x-244169-z Flash Profoto D2 500 air TTL
---	--	--	--	---	--	--	--	--	--

Flash duration t0.1

Normal mode: 1/1,000 s (500 Ws) - 1/7,700 s (1 Ws)

Freeze mode: 1/1,000 s (500 Ws) - 1/13,500 s (1 Ws)

Flash duration t0.5

Normal mode: 1/2,600 s (500 Ws) - 1/17,000 s (1 Ws)

Freeze mode: 1/2,600 s (500 Ws) - 1/63,000 s (1 Ws)

F-stop @ 2m / 100 ISO

45 8/10 with Magnum Reflector

Beam angle

No data

Field angle

No data

Color temp stability

±150 K over range. ±20 K flash to flash

Continuous light

Lamp type

Halogen (GY 6.35)

Max luminous flux (lumen)

No data

Max illuminance @ 1meter (lux)

No data

Color temperature

3200 K

Beam angle

No data

Field angle

No data

Max power

300 W

Wireless connectivity
Built-in connectivity
Profoto AirTTL

Frequency band
2.4 GHz (2404 to 2479.3 MHz)

Supported Air functions
Sync and remote control (Air 1 and Air 2)

Number of Air channels
100 (1-100)

Control flash power using absolute values
Yes (with Air2 mode compatible remote)

Number of groups per Air Channel
6, (TTL operation: 3 (A-C), manual operation: 3 (D-F))

Operating range
Normal sync and remote control 0.5-100 m (1.5-330 ft)

Connectors
Sync
1x 3.5 mm socket (mini-phone)

Other
USB Micro

Powering
Power supply
100-127V/200-240V, 50/60 Hz (nominal)

Mains fuse requirement
6A/230V, 10A/120V

Other
Firmware update

via USB Micro

Operation temperature

+10 C to +35 C (-10 C to +50 C with reduced performance)

Storage temperature

Store in normal indoor conditions

Photocell/IR-slave

Si

Measurements

Width

13 cm / 5.5 in

Length

31 cm / 12.2 in

Height

18 cm / 7.1 in

Weight

3.0 kg / 6.6 lbs Chiudi