


Canon 814 auto zoom Cinepresa (1 EUR)



Luogo **Sicilia, Ragusa**
<https://www.annunci.it/x-585236-z>

Cinepresa Super 8 Canon 814 Autozoom in rare condizioni;\r
\r
è presente la scatola originale dell'epoca con la valigia di trasporto originale Canon, completa delle sue chiavi di chiusura e tracolla mai utilizzata. con stand metallico\r
\r
Tappo obiettivo ed oculare in gomma originali.\r
\r
da testare, pezzo da museo il dispositivo funziona ma non viene provato da tempo, non si accettano reclami\r
\r
\r
Di seguito i dati tecnici:\r
\r
marketed in March 1967\r
\r
silent super 8 cartridge\r
\r
image size: 4.2 x 5.7 mm\r
\r
lens: Canon Zoom Lens C8 f : 1.4 \ F: 7.5-60 mm\r

 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z	 Canon 814 auto zoom Cinepresa https://www.annunci.it/x-585236-z
--	---	---	---	--	---	---	---	---	---

\r
viewfinder: single-lens reflex type with adjustable eyepiece: -3 to +2 diopter\r
\r
viewfinder information: aperture value, exposure meter needle, over/under exposure warnings and film ending indicator\r
\r
exposure: auto and manual exposure control; TTL Servo EE with a CdS exposure meter\r
\r
metering range: 250 ASA, f/1.4, 12 fps - 16 ASA, f/22, 24 fps\r
\r
film speed: automatic between 16/25 and 160/250 ASA (daylight/tungsten) (1)\r
\r
ASA notching: no-pin = slide\r
\r
filming speed: 12, 18, 24 fps, single frame\r
\r
shutter opening angle: 155 degrees\r
\r
shutter speed:\r
\r
- 1/29 seconds at 12 fps\r
\r
- 1/43 seconds at 18 fps\r
\r
- 1/58 seconds at 24 fps\r
\r
CCA filter: built-in 85A filter, automatically cancelled with loading of a daylight type film cartridge; manual cancellation is possible\r
\r
sound: no\r
\r
remote control socket: yes\r
\r
cable release socket: yes\r
\r
movie light contact: no\r
\r
film counter: automatic resetting by opening the side cover\r
\r
handle: retractable, chamber for penlight batteries\r

\r
film drive motor: DC micromotor\r
\r
battery check button: yes\r
\r
power source: 4 x AA batteries \ 2 x 1.3 V(PX625) button cells for light meter\r
\r
weight: 1720 g\r
\r
dimensions: 63 x 107 x 237 mm\r
\r
tripod socket: 1/4"\r
\r
made in Japan by Canon\r
\r
(1) 16/25, 25/40, 40/64, 64/100, 100/160, 160/250 and 250/ 400 ASA.\r
\r
\r

-----\r

L'oggetto di questa asta è venduto "così com'è". Se un oggetto non è stato testato, il rischio che non funzioni è a carico dell'acquirente. Ciò significa che dopo la vendita non è possibile avanzare alcun reclamo in merito alla funzionalità dell'oggetto, a meno che non corrisponda alla descrizione sottostante/superiore.\r

-----\r

\r
\r
\r
\r
\r
\r
\r Chiudi